

FLECK® 2750

1-INCH CONTROL VALVE

IDEAL FOR RESIDENTIAL OR COMMERCIAL FILTER AND SOFTENER APPLICATIONS

FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 26 GPM with a backwash of 25 GPM

Backwash capability accommodates softener tanks up to 30" and filter up to 21" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Time-tested, hydraulically-balanced piston for service and regeneration

Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

OPTIONS

Filter or softener control valves

No hard water bypass piston

Brine cam auxiliary switch

Electromechanical timer auxiliary switch

Hot water

Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration

Manual lever operations

NXT- Network(e)10(vuses on-T)40(-)TJ ET EM

VALVE SPECIFICATIONS

| | |
|----------------|------------------|
| Valve Material | Lead-free brass* |
| Inlet/Outlet | 1" NPTM/BSPM |
| Cycles | 3 or 5 |

FLOW RATES (50 PSI INLET) - VALVE ALONE

| | |
|---------------------------|--------|
| Continuous 15 psi drop | 26 GPM |
|---------------------------|--------|



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 WWW.PENTAIRAQUA.COM CUSTOMER CARE: 800.279.9404 tech-support pentair.com

A P B P A P
P
40737 RE E J L 14 2013 P R E L L C A R R